

In the Claims

1. (previously presented) A video imaging system, comprising:
a camera head for transmitting image data;
a camera control unit for receiving and processing said image data from said camera head;
a storage device accessible by said camera control unit;
a program stored on said storage device;
said program executing on said camera control unit for enabling said camera control unit to process said image data.
2. (previously presented) The video imaging system according to claim 1, wherein said camera control unit comprises a configurable hardware device.
3. (previously presented) The video imaging system according to claim 2, wherein said program configures said configurable hardware device.
4. (previously presented) The video imaging system according to claim 1, wherein said camera control unit comprises a programmable hardware device.
5. (previously presented) The video imaging system according to claim 4, wherein said program programs said programmable hardware device.
6. (original) The video imaging system according to claim 1, wherein said camera control unit comprises: at least one reconfigurable hardware device, from the group consisting of field programmable gate arrays, and computer programmable logic devices; and at least one programmable hardware device, from the group consisting of digital signal processors, and microprocessors.

7. (original) The video imaging system according to claim 6, wherein said program configures said reconfigurable hardware device of said camera control unit to enable it to process said image data from said camera head; and wherein said programmable hardware device executes said program to enable said camera control unit to process said image data from said camera head.

8. (original) The video imaging system according to claim 1, wherein said storage device is located within said camera head.

9. (original) The video imaging system according to claim 1, wherein said storage device is located within said camera control unit.

10. (original) The video imaging system according to claim 1, wherein said storage device includes a removable, replaceable memory unit.

11. (original) The video imaging system according to claim 1, wherein said storage device is remotely accessible.

12. (original) The video imaging system according to claim 11, wherein said storage device is an Intranet location.

13. (original) The video imaging system according to claim 11, wherein said storage device is an Internet location.

14. (original) The video imaging system according to claim 1, wherein said program enables said camera control unit to issue commands to said camera head.

15. (previously presented) The video imaging system according to claim 14, wherein said camera head sends confirmation to said camera control unit that said commands were received.

16. (original) The video imaging system according to claim 14, wherein said camera head adjusts operating characteristics in response to said camera control unit commands.

17. (original) A video imaging system, comprising:
a camera for transmitting image data;
a camera control unit for receiving and processing the image data from said camera;
a storage device accessible by said camera control unit;
software executing on said camera control unit for receiving a program stored on said storage device; and
said program executing on said camera control unit for modifying hardware of said camera control unit for receiving the image data.

18. (previously presented) The system according to claim 1, further comprising software executing on said camera control unit for determining when said camera head is in communication with said camera control unit.

19. (previously presented) The system according to claim 1, further comprising software executing on said camera control unit for downloading said program when said camera head is in communication with said camera control unit.

20. (previously presented) The system according to claim 1, wherein the storage device is a remote location.

21. (original) The system according to claim 20, wherein said remote location is an Internet location.

22. (previously presented) A video imaging system, comprising:
a camera for transmitting image data;
a camera control unit for receiving and processing the image data from said camera;
a storage device accessible by said camera control unit;
a program stored on said storage device;
software executing on said camera control unit for determining when said camera is in communication with said camera control unit;
said program executing on said camera control unit for configuring hardware of said camera control unit; and
said program executing on said camera control unit for enabling said camera control unit to process the image data.

23. (original) The video imaging system according to claim 22, wherein the configurable portion further comprises a field programmable gate array.

24. (original) The video imaging system according to claim 23, wherein said program configures said field programmable gate array of said camera control unit to enable it to process image data from said camera.

25. (original) The video imaging system according to claim 22, wherein said program enables said camera control unit to issue commands to said camera and camera sends confirmation to said camera control unit that said commands were received.

26. (original) The video imaging system according to claim 22, further including a second storage device and processed image data is stored on said second storage device.

27. (currently amended) A video imaging system, comprising:
a camera control unit for receiving and processing image data;
a program located on a storage device for enabling said camera control unit to process the image data;
a configurable hardware device located on said camera control unit for processing the image data;
a processor located on said camera control unit for retrieving and executing said program; and
said program executing on said processor for enabling said configurable hardware device and enabling said camera control unit to process the image data.

28. (original) The video imaging system according to claim 27, further comprising a pre-existing program located on said configurable hardware device for processing the image data.

29. (original) The video imaging system according to claim 28, wherein said program executing on said processor overwrites said pre-existing program.

30. (original) The video imaging system according to claim 27, wherein said configurable hardware device further comprises a non-overwritable portion for requesting said program.

31. (original) The video imaging system according to claim 30, wherein said non-overwritable portion loads said program.

32. (currently amended) A method for video imaging, comprising the steps of:
- providing a camera for transmitting image data;
 - providing a camera control unit for processing the transmitted image data;
 - determining when the camera is in communication with the camera control unit;
 - retrieving a program from a storage device for enabling the camera control unit to be compatible with the camera;
 - executing the program on the camera control unit; and
 - modifying a hardware device of the camera control unit to enable the camera control unit to process image data transmitted from the camera.